



Maxi Slab

Fire and Acoustic Insulation for use with SRS Maxiboard

Maxi Slab is a semi rigid, non-combustible rock mineral wool slab designed to deliver high performance acoustic and thermal insulation. Maxi Slab has been specifically selected and is endorsed for use with all Sound Reduction Systems' Part E and Fire rated Maxiboard details (wall and ceiling).

Maxi Slab Benefits:

- BRE Green Guide Rating of A+
- Zero Global Warming Potential
- Zero Ozone Depletion Potential
- Classed as A1 Non combustible
- Thermal conductivity of 0.035W/Mk



Physical Properties:

Density: 45 kg / m³

Size: 1200 x 600mm

Thicknesses: 25mm / 50mm / 100mm.

This pack:

25_{mm}

Pack Contains:

20No. 1200x600mm Slabs
(14.4m²)

50_{mm}

Pack Contains:

10No. 1200x600mm Slabs
(7.2m²)

100_{mm}

Pack Contains:

5No. 1200x600mm Slabs
(3.6m²)

Handling and storage

Maxi Slab is easy to handle, install and cut to size, where necessary. Maxi Slab is supplied in polythene packs which are designed for short term protection only. For longer term protection on site, the products should either be stored indoors, or under cover and off the ground. Maxi Slab should not be left permanently exposed to the elements.



**sound
reduction
systems**

Manufacturers of Acoustic Insulation Products

Sound Reduction Systems Ltd
Adam St, Off Lever St, Bolton BL3 2AP
Tel: +44 (0)1204 380074 · Fax: +44 (0)1204 380957
E-mail: info@soundreduction.co.uk
Web: www.soundreduction.co.uk